

MOUNTAIN GROUT- MG15

EPOXY SYSTEM ANCHORING

Description

MG15 is a 100% solids, two-component, fast setting anchoring epoxy. MG15 is moisture insensitive and will bond to wet or dry concrete, even underwater. MG15 is commonly used to anchor reinforcing bars, smooth dowels, threaded rod and ties into concrete. The thixotropic paste may be used with screen tubes to anchor rods in unreinforced masonry or brick. MG15 can be used vertically or horizontally.

Features

- Meets criteria for ASTM C-881, Type I, II, IV & V Grade 3, Class A, B & C
- Rapid cure; Less than 1 hour
- Bonds to wet or dry concrete; even underwater
- Easily mixed
- Applied horizontally or vertically
- Moisture insensitive

Typical Information

Test Type	Results	Test Method
Compressive Strength	14000 psi (min)	ASTM D-695
Tensile Strength	7250 psi (min)	ASTM D-638
Elongation	1% minimum	ASTM D-638
Cure Time @ 75°F	1 hour	
Shore D Hardness	87-82	
Pot Life @ 75°F (½ gallon)	10 minutes	
Mix Ratio	1:1 by volume	
Color	Grey	

Packaging

2 & 10 Gallons
22 oz. & 11 oz. Cartridges

READ THE SAFETY DATA SHEET BEFORE USING MOUNTAIN GROUT PRODUCTS!