

# MOUNTAIN GROUT- MGP 168

## HYBRID POLYUREA SYSTEM

### Description

Mountain Grout MGP 168 is a two-component hybrid polyurea, elastomeric joint filler. The system is used to fill and protect joints in industrial concrete floors subjected to heavy hard-wheeled vehicles. It is ideal for spalled joint repair, random joint filling, patching, etc. Unique properties of this elastomer are its rapid cure and insensitivity to moisture.

### Typical Application

- Concrete Floors

### Advantages

- 100 % solids
- Excellent resistance and durability
- Outstanding adhesion
- May be used in cold environments, such as walk in coolers and freezers
- Non-hazardous shipping
- Non-flammable
- Cures inert, non-toxic permanent seal

### Typical Information

Physical Properties - Liquid			
	MGP 168 "A"	MGP 168 "B"	Test Method
Viscosity	1500-1800 cps	1400-1500 cps	ASTM D-2196
Specific Gravity	1.06-1.18	1.059-1.09	ASTM D-1475
Color	Clear, Light Yellow	Grey	
Flash Point	>250°F	>250°F	ASTM D-92
Physical Properties - Cured			
Shore A Hardness	85		ASTM D-2240
Shore D Hardness	38		ASTM D-2240
Tensile Strength	810 psi		ASTM D-638
Elongation	88%		ASTM D-412
Tear Strength	145 pli		ASTM D-624
Toxicity	Non-Toxic		

### Typical Reaction Profile

At 74°F the gel time is about 4 minutes when mixed at a ratio of one to one by volume. Traffic ready time is about one hour.

### Standard Packaging

Mountain Grout MGP 168 is available in 250 gallon totes, 50 gallon drums, 5 gallon pails and 600 mL dual cartridges.

**Read and understand the SDS prior to use.**



# Green Mountain International, LLC

**Application Equipment:** Contact Green Mountain International, LLC for equipment recommendations for the particular application and conditions.

**Personal Protection:** Read SDS for complete details. For professional use only. Avoid breathing vapors – use in well-ventilated area only or use self-contained respiratory protection in confined spaces. Avoid skin contact – wear protective gloves. Avoid eye contact – wear eye protection. Do not ingest.

**First Aid:** In case of eye contact, flush with large amounts of water and get medical attention. For skin contact, wipe excess liquid from skin and wash with soap and water. If breathing is difficult, give oxygen and get medical attention.

**Safety Precaution:** During the chemical reaction, polyurethane products release heat via an exothermic reaction. When polyurethane products are applied in substantial quantities, exothermic reactions may generate enough heat to become a fire hazard. All necessary precautions should be taken to avoid the creation of a situation in which a fire could occur. Contact Green Mountain International, LLC for further information.

**Storage and Shelf Life:** Product is moisture sensitive. Store in original sealed containers at temperatures between 60°F and 90°F (15°C-32°C). Opened containers must be handled properly to prevent moisture contamination. Shelf life is 12 months when properly stored.

**Clean-Up of Spills or Leakage:** With adequate ventilation and appropriate personal protective equipment, cover the spill area with absorbent material such as clay, or vermiculite and transfer to metal waste containers. DO NOT RESEAL CONTAINER AS REACTION OF CONTAMINATED MATERIAL CAN CREATE PRESSURE. Wash area with decontamination solution (5-10 % solution of sodium carbonate). Dispose of waste in accordance with Federal, State and local regulations.

**Shipping Information:** Shipping Class USDOT Class 55; USDOT Hazard Classification: Non-Hazardous.

**Warranty Information:** This limited warranty is limited to the replacement of the materials which are defective. Green Mountain International, LLC makes no other warranty, expressed or implied, and makes no warranty of merchantability or fitness for a particular purpose. This limited warranty does not include any transportation charges or costs of installation or any liability for direct, indirect, consequential, or punitive damages or delay, whether or not the undersigned has been advised of such claims. THE FOREGOING LIMITED WARRANTY IS THE SOLE WARRANTY FOR THE PRODUCT. THERE ARE NO OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, THE WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

**Physical Property Values:** PLEASE NOTE, this Technical Data Sheet is intended as a *general guide* to provide assistance regarding typical physical characteristics of the product. However, the specific values are affected by various factors, including, but not limited to, ambient temperature, water temperature, humidity, water pH, reaction under confinement, and the presence of chemicals or debris in the reaction area. Applicators are encouraged to perform sample tests with the variables found on site to get the best possible indication of the product's physical properties for the specific job.



**Green Mountain International, LLC**