# SAFETY DATA SHEET

# Mountain Grout Flexible

## Section 1: Product and Company Identification

**Trade Name:** Mountain Grout
**Product Name:** Flexible

**Manufacturer:**
Green Mountain International, LLC
235 Pigeon Street
Waynesville, NC 28786
Phone 800-942-5151 US/Canada * 828-456-9970 International

**24 Hour Emergency Telephone Numbers:**
CHEMTREC United States 800-424-9300 * International 703-527-3887

## Section 2: Hazards Identification

### GHS Classifications

**Health:**
Acute Toxicity (Inhalation), Category 4
Skin Irritation, Category 2
Eye Irritation, Category 2A
Respiratory Sensitization, Category 1
Reproductive Toxicity, Category 1B
Skin Sensitization, Category 1
Target Organ Toxicity (Single Exposure), Category 3
Target Organ Toxicity (Repeated Exposure), Category 2

### GHS Label


Health hazard


Exclamation mark

**Signal Word:** Danger.

### Hazard Statements

H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H319: Causes serious eye irritation.
H332: Harmful if inhaled.
H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335: May cause respiratory irritation.

H360: May damage fertility or the unborn child.
H373: May cause damage to respiratory system through prolonged or repeated exposure.

**Precautionary Statements**

**Prevention:**

P260: Do not breathe mist, vapors, and spray.
P264: Wash skin thoroughly after handling.
P271: Use only outdoors or in a well-ventilated area.
P272: Contaminated work clothing should not be allowed out of the workplace.
P280: Wear protective gloves, protective clothing, eye protection and face protection.
P284: In case of inadequate ventilation wear respiratory protection.

**Response:**

P302+P352: IF ON SKIN: Wash with plenty of soap and water.
P362: Take off contaminated clothing.
P333+P313: If skin irritation or rash occurs: Get medical attention.
P304+P340: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P342+P311: If experiencing respiratory symptoms: Call a POISON CENTER or physician.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313: If eye irritation persists: Get medical attention.
P308+P313: IF exposed or concerned: Get medical advice.
P314: Get medical advice if you feel unwell.

## Section 3: Composition/Information on Ingredients

| Component | % (weight) | Product Identifier |
|---|---|---|
| MDI Prepolymer | 30-40 | CAS No. 59675-67-1 |
| 4,4'-Diphenylmethane diisocyanate | 20-30 | CAS No. 101-68-8 |
| Polymeric diphenylmethane diisocyanate | 20-30 | CAS No. 9016-87-9 |
| 1,3-dioxolan-2-one, 4-methyl- | 5-10 | CAS No. 108-32-7 |
| Dibutyltin dilaurate | ≤ 0.5 | CAS No. 77-58-7 |

## Section 4: First Aid Measures

**Eyes:** Immediately flush eyes with plenty of water. Remove contact lenses, if present. Seek medical attention if irritation persists.

**Skin:** Immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Seek medical attention if irritation or rash occurs.

**Ingestion:** If person is conscious, wash out mouth with water. Do not induce vomiting unless instructed to do so by a poison center or physician.

**Inhalation:** Move person to fresh air. Seek medical attention if symptoms of respiratory distress occur. Symptoms may be delayed for several hours.

## Section 5: Firefighting Measures

**Extinguishing Media:** Water fog, foam, dry chemical, or carbon dioxide.

**Hazardous Combustion Products:** Carbon oxides, nitrogen oxides, isocyanates, and trace amounts of hydrogen cyanide.

**Explosion Hazards:** Water contamination produces carbon dioxide gas. This may cause pressurization or explosion of containers.

**Fire Fighting Equipment:** Exposed firefighters must wear NIOSH-approved positive pressure self-contained breathing apparatus with full-face mask and full protective clothing.

## Section 6: Accidental Release Measures

**Personal Protection:** Wear protective equipment listed in Section 8.

**Small Spill:** Isolate the area and prevent entry of unnecessary and unprotected personnel. Do not walk through or otherwise scatter spilled product. Absorb with dry chemical absorbent. Place in a chemical waste container.

**Large Spill:** Same procedure as for a small spill. Prevent entry into waterways, sewers, basements, or confined areas. Allow to stand uncovered 48 hours before closing the waste container.

**Comment:** Avoid using earth, sand, and clay as an absorbent as these can be wet. Isocyanates react with water to form carbon dioxide. Carbon dioxide functions as a blowing agent, causing the product to foam. Allow the waste container to stand uncovered 48 hours before closing. Reaction with water can be slow. Build-up of carbon dioxide in a closed container can rupture the container.

**General Procedures:** Clean spill area with a decontamination solution. Suggested formulation: Sodium carbonate (5-10%), liquid detergent (1-2%), water (88-94%). Alternate formulation: Concentrated ammonia (3-8%), liquid detergent (1-2%), water (90-96%). Ensure adequate ventilation to prevent overexposure of ammonia.

## Section 7: Handling and Storage

**Handling:** Do not get in eyes, on skin or on clothing. Wash hands before eating, drinking, or smoking. Do not breathe vapors or mists. Use only with adequate ventilation. Keep container closed when not in use. Do not reseal if contaminated. Keep away from heat and flame.

**Storage:** Store in tightly closed containers in cool, dry, and well-ventilated area away from heat or sources of ignition. Keep out of direct sunlight.

**Storage Temperature:** 4.4°C - 32.2°C (40°F - 90°F)

## Section 8: Exposure Controls/Personal Protection

**Exposure limits:**

| Component | CAS No. | OSHA/PEL | ACGIH/TLV |
|---|---|---|---|

| | | | |
|---|---|---|---|
| 4,4'-Diphenylmethane diisocyanate | 101-68-8 | 0.02 ppm (Ceiling)<br>0.20 mg/m$^3$ (Ceiling) | 0.005 ppm<br>0.051 mg/m$^3$ |
| Dibutyltin dilaurate | 77-58-7 | 0.1 mg/m$^3$ | 0.1 mg/m$^3$<br>0.2 mg/m$^3$ (STEL) |

**Engineering Controls:** Local exhaust ventilation used in combination with general ventilation as necessary to control air contaminates.

**Eyes and Face:** Wear a face shield and chemical safety glasses or goggles.

**Skin:** Wear impervious gloves. Cover exposed skin.

**Respiratory:** For airborne exposure above the exposure limit(s), wear a NIOSH approved air-purifying respirator equipped with organic vapor cartridges. For situations where the atmospheric levels may exceed the level for which an air-purifying respirator is effective, use a positive-pressure air-supplying respirator.

**Work Hygienic Practices:** Avoid eating, drinking, or smoking while using this material. Wash hands thoroughly after handling.

## Section 9: Physical and Chemical Properties

| | |
|---|---|
| Appearance | Light yellow liquid. |
| Odor | Slightly musty. |
| Autoignition Temperature | Not established. |
| Freezing Point | Not established. |
| Boiling Point | Not established. |
| Flash Point (Closed Cup) | > 93.3°C (200°F) |
| Vapor Pressure | < 0.001 mmHg at 25°C (77°F) |
| Vapor Density (air = 1) | Heavier than air. |
| Solubility in water | Partial. |
| Specific Gravity (water = 1) | 1.15 at 25°C (77°F) |
| Viscosity (centipoise) | 500 at 25°C (77°F) |

## Section 10: Stability and Reactivity

**Stability:** Stable.

**Hazardous Polymerization:** Can be caused by elevated temperatures.

**Hazardous Decomposition Products:** Carbon oxides, nitrogen oxides, isocyanates, and trace amounts of hydrogen cyanide.

**Incompatible Materials:** This product will react with any materials containing active hydrogens such as water, alcohol, amines, bases, and acids. The reaction with water is very slow under 50°C (122°F) but is accelerated at higher temperatures.

## Section 11: Toxicological Information

**Acute:**

| Component | Oral $LD_{50}$ (rat) | Dermal $LD_{50}$ (rabbit) | Inhalation $LC_{50}$ (rat) |
|---|---|---|---|
| 4,4'-Diphenylmethane diisocyanate | > 10000 mg/kg | > 9400 mg/kg | 0.49 mg/l/4h |
| 1,3-dioxolan-2-one, 4-methyl- | 29100 mg/kg | 23800 mg/kg | |
| Dibutyltin dilaurate | > 2000 mg/kg | > 2000 mg/kg | |

**Carcinogenicity:**

IARC: Not regulated as a carcinogen.
NTP: Not regulated as a carcinogen.
OSHA: Not regulated as a carcinogen.

## Section 12: Ecological Information

**Ecotoxicological Information:**

MDI: $LC_{50}$ (zebra fish) > 500 mg/l/96h; $EC_{50}$ (Daphnia magna) > 500 mg/l/24h

## Section 13: Disposal Considerations

**Disposal Method:** Dispose in accordance with local, state, provincial or national regulations.

**Empty Container:** Decontaminate and pass to an approved drum recycler or destroy.

**RCRA/EPA Waste Information:** If discarded in its purchased form, this material is not a RCRA hazardous waste.

**General Comments:** The generation of waste should be avoided or minimized whenever possible. Chemical waste, even small quantities, should never be poured into drains, sewers, or waterways.

## Section 14: Transport Information

**U.S. DOT:** Not regulated.
**ICAO/IATA:** Not regulated.
**IMO/IMDG:** Not regulated.

## Section 15: Regulatory Information

**United States**

**SARA Title III (Superfund Amendments and Reauthorization Act)**

311/312 Hazard Categories: Acute, Chronic, Reactive.

313 Reportable Components:

| Component | CAS No. |
|---|---|
| 4,4'-Diphenylmethane diisocyanate (Category Diisocyanate Compounds) | 101-68-8 |
| Polymeric diphenylmethane diisocyanate (Category Diisocyanate Compounds) | 9016-87-9 |

**CERCLA (Comprehensive Environmental Response and Liability Act)**

| Component | RQ (lbs) |
|---|---|
| 4,4'-Diphenylmethane diisocyanate | 5000 |

**TSCA (Toxic Substances Control Act):** All components are in TSCA inventory**.**

**RCRA Status:** If discarded in its purchased form, this material is not a RCRA hazardous waste.

**National Response Center:** Any spill or release to the environment above the RQ must be reported to the National Response Center (800-424-8802).

## Section 16: Other Information

Date Issued: October 5, 2005
Revised: August 4, 2022 Rev #11

**Manufacturer Disclaimer:** The information in this SDS was obtained from sources that we believe are reliable. The information is provided without warranty, implied or expressed, concerning accuracy. The manufacturer assumes no legal responsibility for use or reliance on this information. This SDS is provided solely for the purpose of conveying health, safety, and environmental information. This SDS is not a specification data sheet. Some of the information and conclusions may be derived from sources other than test data on the material itself.

**Abbreviations and Acronyms:**

| | |
|---|---|
| ACGIH | American Conference of Governmental Industrial Hygienists |
| CAS | Chemical Abstracts Service |
| $EC_{50}$ | Median effective concentration |
| EINECS | European Inventory of Existing Commercial Chemical Substances |
| GHS | Globally Harmonized System of Classification and Labelling of Chemicals |
| IARC | International Agency for Research on Cancer |
| IATA | International Air Transport Association |
| ICAO | International Civil Aviation Organization |
| IMDG | International Maritime Dangerous Goods |
| IMO | International Maritime Organization |
| $LC_{50}$ | Lethal concentration to 50% of exposed laboratory animals |
| $LD_{50}$ | Lethal dose to 50% of exposed laboratory animals |
| TWA | Time-weighted average |
| TLV | Threshold limit value |
| NIOSH | US National Institute of Occupational Safety and Health |
| NE | Not established |
| NTP | US National Toxicology Program |
| OEL | Occupational exposure limit |
| OSHA | US Occupational Safety Health Administration |
| PEL | Permissible exposure limit |
| RQ | Reportable quantity |
| STEL | Short term exposure limit |
| U.S. DOT | United States Department of Transportation |